SCREW DRIVEN ACTUATORS > MSA-DRT ACTUATOR

## **MSA-DRT ACTUATOR**



## SCREW PITCH (MM) 5 10 20 STANDARD TRAVELS (MM) Min 150 - Max 650 in 25 increments HOW TO BUILD YOUR MSA-DRT: MSA - DRT - N - X - A X 1- X Screw Pitch Motor Mount Standard Travels



SCREW DRIVEN ACTUATORS > MSA-DRT ACTUATOR

## **MSA-DRT ACTUATOR**

SPECIFICATIONS  Specifications	
Nut Type	Ball Screw
Maximum Speed - mm/s	325 (05), 650(10), 1250 (20)
Maximum Load - lbs.	500
Repeatability - mm	+/- 0.15
Efficiency	90%
Cart Guide	Linear bearing with profile rail
Motor Sizing Information	
Weight of Cart - lbs.	7.2
Travel per Revolution - mm	5 (05), 10 (10), 20 (20)

SPECIFICATIONS	
Weight w/motor adaptor	
Min - Ibs.	26.4
Increment - lbs.	2.2
Travels	
Standard Travels - min / max - mm (25 mm increments)	150 to 650

## **Features**

- · Commercial grade actuator with ball screw drive
- Extruded base profile and cart top allows multi-side mounting and attachment of components using T-nut fasteners
- Sealed linear profile rail and bearing guidance
- Can easily combine with MacSTANDARD belt actuators to create hybrid multi-axis systems
- Optional bellows seals are available
- Motor adaptors or MPG gearboxes are available accessories
- Four 20 series linear bearings with 2 covered steel profile rails

All Macron actuators and belt drives are covered by our 1-Year Warranty