
BELT DRIVEN ACTUATORS > MSA-SBH BELT DRIVE

## **MSA-SBH BELT DRIVE**





BELT DRIVEN ACTUATORS > MSA-SBH BELT DRIVE

**SPECIFICATIONS** 

# **MSA-SBH BELT DRIVE**

Specifications	
Motion	Horizontal or Vertical
Max Speed - horizontal [vertical] - mm / sec	15240 [7620]
Max Load - horizontal [vertical] - lbs.	2500 [1250]
Repeatability - mm	+/-0.025
Moment Load Max - in lbs. [Nm]	NONE
Positional Accuracy - mm / meter	+/- 0.4
Acceleration max - G's	20
Beam Dimensions - mm	80 x 98
Ultimate tensile strength of belts - lbs. [N]	10,800 [48,040]
Recommended belt running load - lbs. [N]	2700 [12,015]
Cart Guide	NONE
Motor Sizing Information	
Weight of Drive Pulley - oz. / kgs.	105 / 2.98
Weight of Idler Pulley - oz. / kgs.	92 / 2.60
Weight of Cart - lbs. / kgs.	N/A
Weight of Belt - kgs. based on travel selected	((Travel in meters x 2) + 0.84) x 0.35
Travel per Revolution - mm	280
Pulley Pitch Diameter - mm	89.13
Pulley Material / Width - mm	steel / 50
Breakaway Torque - oz in.	N/A
Coefficient Friction	N/A
Rolling Resistance - lbs. / kgs.	N/A

Weight	
Weight - min. travel unit (150 mm) - lbs. / kgs.	41.7 / 18.9
Weight - additional 25 mm of travel - lbs. / kgs.	0.28 / 0.13
Travels	
Standard Travels - min max - mm (25 mm increment)	150 / 5625

## **Features**

**SPECIFICATIONS** 

- · Extruded aluminum actuator body with T-slots for ease of mounting
- · Easy to adjust belt tensioner
- · One piece, machined and stress proof shafted pulley
- · Zero backlash belt to pulley design
- · Corrosion resistant components

### Macron Solutions Since 1987

Macron Guarantee

MACRON DYNAMICS, INC. 100 Phyllis Drive Croydon, PA 19021 © 2014 MACRON DYNAMICS, INC.

1-800-MACRON-1 (1-800-622-7661) Phone: 267-557-3590 Fax: 215-443-0981

All Macron actuators and belt drives are covered by our 1-Year Warranty